

Optimized Corrosion Control Treatment: Pilot-Scale Testing for Portland Water Bureau

Michelle Cheek, PE
Portland Water Bureau

Melinda Friedman, PE
Alex Mofidi, PE
Danbi Won, EIT
Confluence Engineering



2018 PNWS-AWWA
Annual Conference
Tacoma, Washington

Acknowledgements

- Portland Water Bureau

- Michelle Cheek
- Kim Gupta
- Yone Akagi
- Mac Gifford
- Tom Krause

- Confluence

- Alex Mofidi
- Michael Hallett
- Danbi Won

- HDR

- Pierre Kwan

- 1** Corrosion Control Treatment (CCT)
Pilot Testing Set Up and Caveats
- 2** Summary of Findings
- 3** Recommendations
- 4** Next Steps

Why Was Pilot Testing Recommended?

- Confirm bench results
- Determine if more definitive CCT “leader” could be identified
- Use harvested materials with native scales

PWB Corrosion Control Treatment (CCT) Pilot Plant Trailer



PWB Lab Trailer



CCT Pilot Set-Up

- Four water quality scenarios
 - Current Bull Run (pH 8.2)
 - Moderate pH/Alk (8.6/40)
 - Hi pH/lower Alk (9.0/20)
 - Orthophosphate (0.75-1 mg/L P)
- 2 types of testing rigs



Four “material” rigs, each containing three materials harvested from DS

- Brass meters
- Galvanized pipe
- Joints of copper pipe with lead solder

2 PRS stations – 4 coupon chambers

- Lead
- Copper with lead solder
- Galvanized
- Brass

PWB CCT Pilot Trailer – Material Rigs



PWB CCT Pilot Trailer – Process Research Solutions (PRS) Stations

4-Chamber PRS Station



Caveats When Interpreting CCT Pilot Data

- No direct equivalency toward LCR compliance monitoring
 - e.g., 20 µg/L pilot result ≠ 20 µg/L in distribution system
- Cannot compare between rigs or materials– only within rig, for single material using different WQ endpoints
- Importance of Dissolved vs. Particulate
 - Dissolved lead is result of uniform, galvanic, (and perhaps microbial) influenced corrosion
 - Particulate lead associated with release of scale due to hydraulic disturbance, change in water quality, etc.

A Long Story Made Short....

- **Testing Condition**

- Originally pH 8.0 leaving LHTF previous to project
- Raised to pH 8.2 leaving LHTF at onset of project

- **pH Reaching Site was Greater than Expected and Increased Over Time**


- Actual pH at pilot POE was much greater (~8.5) instead of 8.2
- Chemical feed not practical (or necessary?)
- Down-side (variable data, very low alkalinity/DIC, other....)
- Increased stagnation period to 'force' lead release




Filtration!


2 Summary of Findings

Source water vs. Rig 1 Cu/Pb Solder Stagnation pH







Impact of Stagnation on pH




Bigger Picture Thoughts:

- Demonstrates limitations of WQP monitoring
- No way to pair/know residential tap pH conditions associated with LCR results
- Especially important in poorly-buffered waters


Impact of pH on Lead (harvested copper pipe with lead solder)




Scale





Scale



Samples dominated by particulate lead



Particulate Metals: Lead vs. Manganese and Iron



Pb MRL = 0.05 ug/L

Mn MRL = 0.5 ug/L


Findings

- Expected Variability Between Materials
- Site conditions allowed for “passive” testing of moderate pH conditions
 - Approximately pH 8.5-8.6
 - Very low DIC water (no Alkalinity addition)
- Lead release typically >50% particulate
- Particulate release correlated with other metals, indicating scale disturbance/release
- Dissolved lead controlled primarily by end of stagnation pH
- Results Support Bench-Scale Tests
 - Moderate pH control suppresses Pb release in all materials
 - pH reduction with increasing stagnation period
- Acclimated PRS stations provide useful tool to understand metals release

3 Recommendations

Interim Pre-Filtration CCT Recommendation (IPF-CCT)

- pH \geq 8.5 throughout distribution system
- Alkalinity \geq 25 mg/L CaCO₃
 - Increase buffering capacity
 - Increase DIC



Data from modeling completed using Water!Pro V6.3

4 Next Steps

Chemical Selection and Location

- Completing evaluation of pH/alkalinity adjustment options
- To be located at Lusted Hill
- Submit IPF-CCT Report to State
- Design and construct
- Online in 2022

Determine CCT for Filtered PWB Water

- Use of coagulants and potential impacts on galvanic corrosion
- Removal of Natural Organic Matter (NOM)
 - Impacts on metals solubility and biostability
- Changes in disinfection strategies and impacts on ORP, biostability, etc
- Disinfection Byproduct Formation

THANK YOU



confluence
ENGINEERING GROUP LLC




2008 - 2018


517 NE 92nd St, Seattle, WA 98115

206.527.6832 www.confluence-engineering.com

Samples dominated by particulate lead



Particulate Lead vs. Copper



Dissolved Lead vs. Manganese

